

POS & Monitor **SATURN**



A new “ready-made” philosophy

The application of customer experience is evolving rapidly in today's digital age. To fulfill complex vertical market demands and satisfy each customer's expectations, Saturn finds the right balance between standardization and customization from its design.

With modular design advantages, the Saturn brings the contemporary PoS technologies which combine functionality and flexibility to satisfy various market requirements while still keeping the costs affordable for its clients. Saturn provides a wide variety of configuration options and branding tools that allow businesses to create a semi-custom model to best suit your specific business needs.



45mm Ultra slim



Easy service storage



Quiet and silent operation
(Saturn 415&615)



Fanless and energy-efficient
(Saturn 415&615)



Mix'n'match, make it your own

1 STANDS & MOUNTS



W-Stand
With built-in cable organizer



L-Stand
With ample storage space for power brick



E-Stand
With height-adjustable dual-hinge design



VESA Mount
Universal VESA mount kit

2 DISPLAYS



15" LCD



10.4" LCD



VFD



LCM

3 READERS



MSR & iButton Detector



Biometric Fingerprint Recognizer



MSR



iButton Detector



RFID Reader



Barcode Scanner

4 CORE SYSTEM

Model	Saturn 415	Saturn 615	Saturn 715	
Display	LCD Panel	15" TFT LCD		
	Resolution	1024 x 768		
	Brightness	300 [cd/m ²]		
	Touch Screen	Flat PCAP Touch (USB)		
System Configuration	CPU	RK3288 Quad-core Cortex-A17 1.6GHz	Intel® Celeron® J1900 2.4GHz Intel® Core™ i3 3.4GHz / Intel® Core™ i5 2.7GHz	
	Memory	Onboard DDR3 2GB / 4GB	DDR3L SO-DIMM, max. 8GB	DDR3L SO-DIMM, max. 16GB
	Storage	eMMC 16GB / 32GB; Micro SD (Extension)	2.5" SATA HDD or SSD	2.5" SATA HDD or SSD
	O/S	Android 7.1	Windows 7/ POSReady 7/	Windows 10/
	Compatibility	Linux Kernel 3.0 or above	Windows 10/ Linux Kernel 3.0 or above	Linux Kernel 4.0
	Adapter	60W (12V/5A)	60W (12V/5A)	120W (24V/5A)
	LED Indicator	Power LED indicator		
	Certification	CE / FCC / CB / LVD		
	Temperature	0°C to 40°C (operation), -25°C to 70°C (storage)		
	External I/O Ports	USB	4 x USB 2.0, 1 x USB OTG	3 x USB 2.0, 1 x USB 3.0
COM		1 x DB9	3 x RJ50 (5V/12V selectable)	3 x RJ50 (5V/12V selectable)
LAN		1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet
VGA		N/A	1 x DB15	1 x DB15
HDMI		1 x HDMI	N/A	N/A
Cash drawer		1 x RJ12	1 x RJ12	1 x RJ12
Speaker		2 x 1W Speaker	N/A	2 x 1W Speaker
DC out		N/A	DC12V out	DC12V out
DC in		DC12V in	DC12V in	DC24V in

5 SYSTEM COLORS



White



Black



Red



Green



Yellow



Silver



White



Tunisie

Sfax : Av de la liberté, Im El Ilkan 3^{ème} étage, B11 CP. 3027
Tél : +216 74 415 055 Fax: +216 74 415 044

Tunis : Tunis : 7, rue du Lac Côme, Imm. Nessima, 1^{er} étage, B1 & B2, Les Berges du Lac, CP.1053.
Tél. : +216 71 655 261

Sousse : Av Yasser Arafat, Résidence Chaima, 4^{ème} étage, B 401, Sahloul CP. 4054
Tél. : +216 73 368 115

Algérie

Alger : Cooperative comps 2 villa N° 40, kouba
Tél : +213 (0) 23 70 88 08 - MOB: +213 (0) 541 53 06 42

Sénégal

Dakar : 01, Avenue Pasteur, RDC Bloc Pasteur, CP. 10200, Dakar - Sénégal
Tél : +221 33 821 85 38 - Mob: +221 78 147 82 73

