

AP230 IMPRIMANTE TICKET

Printing	Print Method	Direct Thermal
	Resolution	203 dpi (8 dots/mm)
	Print Speed	Max. 230 mm/s
	Print Width	Max. 72 mm
Interface	Standard	Built-in USB, Serial, Ethernet
Page Mode		YES
Memory	RAM	16 MB
	Flash	4 MB
Programming Language		ESC/POS
Fonts		Alphanumeric; Simplified Chinese; 47 codepages
Barcode		UPC-A, UPC-E, EAN-8, EAN-13, CODE 39, ITF, CODEBAR, CODE 128, CODE 93, QR, PDF417
Graphics		Support bitmap printing with different density and user defined bitmap printing. (Max size of each bitmap is 40 KB, the total : KB)
Indicators	Power	Green
	Error	Red
	Paper Out	Red
Sensors	Standard	Paper out, cover open, cutter jam
	Option	N/A
Power Supply	Input	AC 100V ~ 240V, 50/60Hz
	Output	DC 24V, 2A
Paper	Paper Type	Thermal Receipt Paper
	Paper Width	58 mm/80 mm
	Paper Thickness	0.056 mm - 0.13 mm
	Roll Paper Diameter	Max. Φ 83 mm (O.D.)
	Paper Load	Front paper loading
	Paper Cut	Partial cut
Environment	Operating	0°C - 45°C, 10% - 85% R.H, no-condensation
	Storage	-20°C - 60°C, 10% - 90% R.H, no-condensation
Physical Characteristics	Dimensions	140(L) \times 191(W) \times 127(H) mm
	Weight	1.64 kg
Software	Driver	HPRT Driver: Windows XP, Vista, 7, 8, 10, Linux, Mac
	SDK	WinCE, Win Mobile, Android, iOS



58mm Paper Guide

