

# DITRONETWORK ST9800



Part	Setting	Specification	
The host	CPU	I3 Dual core 2.3 GHz/Dual core 2.0 GHz	
	OS Support	win7 win8 win10 Linux posready 7 above system	
	Display	Display size	15 inch 4:3
		Resolution	1024(RGB)*768
		Brightness	350cd/m <sup>2</sup>
		Contrast ratio	700:1(Typ.)(transmission)
		Touch screen	Pure flat surface capacitance 10 point multi-touch
		Display area	304.1*228.1mm
	RAM	4G	
	Hard Disk	64G SSD, Msata, HDD	
Port	Standard USB	4*USB 2.0+ 2*USB 3.0	
	HDMI	1	
	RS232	2*RS232	
	1* 12V DCout	1	
	VGA	1	
	Audio	1	
	Option port	12V DCout	1* 12V DCout
COM(RS232)		1*COM(RS232)	
Option Peripheral	MSR	LIF-MSR006ISO7811	
	RFID	LIF-RD01 supports mifare one S50,S70 and its compatible TYPE A and B cards	
	IC	LIF-PC/SC supports standard HID protocol and PC/SC protocol	
	IBUTTON-A	comply with the 1-wire protocol	
	Customer display	12inch 16:10(1280*800)	
	VFD	2*20 LED	
	WIFI	11N wireless 300Mbps	
	4G	Optional	
	Speaker	Optional	
Weight	7.5KG		
Certification	CE,FCC,ROHS		



#### Tunisie

Sfax : Av de la liberté, Im El Ilkan 3<sup>ème</sup> étage, B11 CP. 3027  
Tél : +216 74 415 055 Fax: +216 74 415 044

Tunis : Tunis : 7, rue du Lac Côme, Imm. Nessima, 1<sup>er</sup> étage, B1 & B2, Les Berges du Lac, CP.1053.  
Tél. : +216 71 655 261

Sousse : Av Yasser Arafat, Résidence Chaïma, 4<sup>ème</sup> étage, B 401, Sahloul CP. 4054  
Tél. : +216 73 368 115

#### Algérie

Alger : Cooperative comps 2 villa N° 40, kouba  
Tél : +213 (0) 23 70 88 08 - MOB : +213 (0) 541 53 06 42

#### Sénégal

Dakar : 01, Avenue Pasteur, RDC Bloc Pasteur, CP. 10200, Dakar - Sénégal  
Tél : +221 33 821 85 38 - Mob : +221 78 147 82 73

www.asmpos.com  
contact@asm.com.tn

