

Thermal Transfer/ Direct Thermal


## XP-TT424B

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon core inner diameter: 0.5"
- Bartender special edition



# XP-TT424B

Thermal Transfer/ Direct Thermal



<b>Model</b>	<b>XP-TT424B</b>
<b>Resolution</b>	203 DPI
<b>Print method</b>	Thermal Transfer / Direct Thermal
<b>Print spee</b>	127 mm (5") / s Max.
<b>Max.print width</b>	108 mm (4.25")
<b>Max.print length</b>	1778 mm (70")

## Media

<b>Media type</b>	Continuous, gap, black mark, fan-fold and punched hole
<b>Media width</b>	25.4-118mm (1.0"-4.6")
<b>Media thickness</b>	0.06~0.254 mm
<b>Media core diameter</b>	25.4 ~ 50.8 mm (1" ~ 2")
<b>Ribbon length</b>	Max.90m
<b>Ribbon width</b>	25.4mm-110mm (1"-4.3")
<b>Label length</b>	10 mm ~1778 mm
<b>Label roll capacity</b>	127 mm (5") OD(outer diameter)
<b>Ribbon core inner diameter</b>	12.7 mm (0.5 ")

## Performance Features

<b>Processor</b>	32-bit CPU
<b>Memory</b>	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
<b>Interface</b>	Standard:USB Optional:WIFI/Bluetooth/TF card
<b>Sensors</b>	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor

## Fonts/Graphics/Symbologies

<b>Internal fonts</b>	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
<b>1D barcode</b>	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
<b>2D barcode</b>	PDF-417, Maxicode, DataMatrix, QR code
<b>Rotation</b>	0°, 90°, 180°, 270°
<b>Emulaion</b>	TSPL、EPL、ZPL、DPL

## Physical Features

<b>Dimension</b>	246mm × 199mm × 168mm (D × W × H)
<b>Weight</b>	1.62kg

## Reliability

<b>Print head life</b>	30 km
------------------------	-------

## Software

<b>Driver</b>	Windows / Linux / Mac
<b>SDK</b>	Windows / Android / iOS

## Power supply

<b>Input</b>	AC 100-240V
<b>Output</b>	DC 24V, 2.5A

## Options

<b>Factory Options</b>	①Bluetooth module ②WiFi module ③Real clock ④Cutter
<b>Dealer Options</b>	① External paper roll holder ②Paper roll spindle ③Extension board for external paper roll holder ④Shipment waybill box

## Environmental Conditions

<b>Operation</b>	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
<b>Storage environment</b>	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing



### TUNISIE

Sfax: Av de la Liberté, Imm. El Itkan 3<sup>ème</sup> étage, B11, CP. 3027  
☎(+216) 74 415 055 / 📠(+216) 74 415 044  
Tunis: 7, rue du Lac Côme, Imm. Nessima, 1<sup>er</sup> étage, B1, B2 & B3  
Les Berges du Lac, CP.1053. ☎(+216) 71 655 261  
Sousse: Av. Yasser Arafat, Résidence Chaima, 4<sup>ème</sup> étage,  
B 401, Sahloul, CP. 4054. ☎(+216) 73 368 115



### ALGÉRIE

Alger: Cité 420 logements, bâtiment 17 n°1 El Hamiz, Dar  
El Beida, CP. 16033, Alger  
☎+213 770 947 069 / +213 770 945 731



### SÉNÉGAL

Dakar: 25, Avenue Pasteur, RDC Imm. Pasteur, CP. 10200  
☎+221 78 147 82 73 / +221 33 821 85 38



### MAURITANIE

Nouakchott: Tevragh-Zeina, Avenue  
Mokhtar Oulf Daddah  
☎+222 49 12 14 94



### FRANCE

Paris: 128 Rue de la Boétie 75008  
☎+33 6 17 54 78 03

**asm**  
All Soft Multimedia

